



## NOTICE OF SUSPENSION

Due to the suspension of work for non-essential PICC Personnel, we are suspending all procurement Activities starting March 26, 2021.

We will issue a separate Notice of Resumption of Procurement Activities sometime in April 2021.

A handwritten signature in black ink, appearing to read "M. Gonzaga", is positioned above the printed name.

Melpin A. Gonzaga  
BAC Chairman

**SUPPLEMENTAL BID BULLETIN**

**Republic of the Philippines  
PHILIPPINE INTERNATIONAL CONVENTION CENTER  
PICC Complex, 1307 Pasay City  
BIDS AND AWARDS COMMITTEE (BAC)**

March 18, 2021

**SUPPLY OF VARIOUS ELECTRICAL AND ELECTRONICS SUPPLIES,  
PARTS AND MATERIALS**

**ADDENDUM NO. 01**

This Addendum is issued to amend/revise certain provisions of the Bid Documents for the above-captioned procurement. The amendments are, as follows:

I. Section III- Bid Data Sheet

- ITB Clause 20.2
  - Item "b"
    - Sections III, V and VI of the bid documents, signed on each and every page by the bidder's authorized representative;
  - Item "c"
    - Brochures of the items offered:  
Lot I – Item No. 1  
Lot II – All items  
Lot III – Item Nos. **51, 55, 59, and 63**

II. Section VII-Technical Specifications

- Lot I- Supply and Delivery of Electrical Materials
  - Page 24 – Item No. 14. PVC elbow, **90 degrees, 1" dia.**
  - Page 24 – Item No. 19. PVC elbow, **90 degrees, ½" dia.**
  - Page 24 – Item No. 24. EMT elbow, **90 degrees, ½" dia.**
  - Page 25 – Item No. 38. Incandescent bulb, round, 10 to 15 watts
  - Page 25 – Item No. 39. High Power LED bulbs, min. of 27 watts, **min. of 2700 lumens, warmwhite, 100-240VAC, 150 degrees beam angle, Minimum of 15000 burning hours**
  - Page 25 – Item No. 41. LED Electronic driver  
**Philip Advance Lighting**  
**Power factor: 0.95**  
**Power output: 150 watts**  
**Input voltage: 120 to 277 VAC, 50/60Hz**  
**Output voltage: 107 to 214 Vdc**  
**Ballast dimming: Yes**  
**Dimming type: 0-10V dimming**  
**Output current: 0.7 Adc or higher**

- Page 25 – Item No. 42. LED Street Light, min. of 80 watts. 230VAC  
**Luminous flux: Min. of 9,600 lm**  
**Light source: 2 layer of high brightness LED SMD**  
**Color Temperature: Warm White**  
**Materials: Die cast aluminum alloy**  
**Lifetime: 50,000 hours**  
**IP Rating: IP65**
  
- Page 25 – Item No. 43. LED tubes, 15-18 watts,  
**Length: 1.2m**  
**Input voltage: 220V (without ballast)**  
**Beam angle: at least 180 degrees**  
**color Temp.: Daylight**  
**Difuser: Frosted poly carbonated cover**  
**Min. lifetime: 50000 hours**  
**Min. flux: 100 lm**  
**Offered brand must be rosh and UL/ETL approved**
  
- Page 25 – Item No. 44. LED tubes, 4 to 6 watts,  
**Length: 1 ft**  
**Input voltage: 220V (without ballast)**  
**Beam angle: at least 180 degrees**  
**color Temp.: Daylight**  
**Difuser: Frosted poly carbonated cover**  
**Min. lifetime: 50000 hours**  
**Min. flux: 100 lm**  
**Offered brand must be rosh and UL/ETL approved**
  
- Lot III – Supply and delivery of wires and Cables (**offered brand must have PS mark**)

Corrected copies are attached. Bidders are advised to replace their original copies with the corrected copies.

For guidance and information of all concerned.

  
**MELPIN A GONZAGA**  
Chairman

Received by:

\_\_\_\_\_  
(Signature over printed name)  
Telephone/Fax No. \_\_\_\_\_  
Date: \_\_\_\_\_  
Name of Company: \_\_\_\_\_

20.2	<p>Within a non-extendible period of five (5) calendar days from receipt by the bidder of the notice from the BAC that it submitted the LCB, the Bidder shall submit the following documentary requirements:</p> <ul style="list-style-type: none"> <li>a. Certified Photocopy of the CY 2019 Income and Business Tax Returns filed and paid through the BIR Electronic Filing and Payment System (eFPS);</li> <li>b. Sections III and V <i>and VI</i> of the bid documents, signed on each and every page by the bidder's authorized representative;</li> <li>c. Brochure of the items offered for the following items: <ul style="list-style-type: none"> <li>o Lot I – Item No. 1</li> <li>o Lot II – All items</li> <li>o Lot IV Item <i>Nos. 51, 55, 59, and 63</i></li> </ul> </li> <li>d. Company Profile with sketch of office location;</li> <li>e. Certificate of Satisfactory Completion &amp; Acceptance of previous PICC projects undertaken within the last three (3) years, if any.</li> </ul>
21.2	No additional requirement

## Technical Specifications

Item	Qty.	Unit	Specification	Statement of Compliance
<b>Lot I - SUPPLY AND DELIVERY OF ELECTRICAL MATERIALS</b>				
1	99	pc	Lamp Holder, e27, with built-in induction motion sensor switch, 110 to 220VAC, at least 60 watts rated load, 6 meter detection range, adjustable light delay time out from 10 second to 5 minutes	
2	10	pc	Penetrating oil, minimum of 400mL	
3	80	pc	Plug, 2-prong, parallel, heavy duty	
4	25	pack	Cable tie (nylon), 2.5-3.0mm x 6" long (100pcs/pack)	
5	25	pack	Cable tie (nylon), 4.0mm x 12" long (100pcs/pack)	
6	25	pack	Cable tie (nylon), 4.0mm x 8" long (100pcs/pack)	
7	25	pack	Cable tie (nylon), 5.0mm x 12" long (100pcs/pack)	
8	10	can	Spray paint, epoxy primer, gray, 400cc	
9	40	kg	Rags, cotton, white	
10	35	pc	Globe/round acrylic diffuser, clear, 14" diameter	
11	1400	roll	Electrical Tape, PVC, 0.16mm x 19mm x 16 m (min.), UL listed	
12	15	box	Gun tucker staple wire, T25	
13	200	pc	PVC electrical conduiti, 1" dia	
14	78	pc	PVC elbow, <i>90 degrees</i> 1" dia	
15	70	pc	PVC junction box with cover, 4" x 4", 1" dia	
16	140	pc	PVC male adapter with nut, 1" dia	
17	100	pc	PVC coupling, 1" dia	
18	266	pc	PVC electrical conduiti, 1/2" dia	
19	44	pc	PVC elbow, <i>90 degrees</i> 1/2" dia	
20	87	pc	PVC junction box with cover, 4" x 4", 1/2" dia	
21	174	pc	PVC male adapter with nut, 1/2" dia	
22	100	pc	PVC coupling, 1/2" dia	
23	166	pc	Electrical metallic tubing (EMT), 1/2" dia	
24	50	pc	EMT elbow, <i>90 degrees</i> 1/2" dia	
25	60	pc	EMT junction box, 4"x4", 1/2" dia	
26	120	pc	EMT male adapter with nut, 1/2" dia	
27	140	pc	EMT coupling, 1/2" dia	
28	320	pc	C-metal clamp, 1/2" dia	
29	1	pc	NEMA 4X enclosure with cover	
30	5	kg	GI wire #16	
31	50	pair	Construction gloves	
32	1000	pc	Metal screw with tox, Size #10	
33	10	unit	Automatic Voltage Regulator, 300VA, Input-160-240VAC, 6Hz, Output Voltage - 100 and 220VAC, 60Hz	

<b>Lot II - SUPPLY AND DELIVERY OF LIGHTING MATERIALS</b>			
34	150	pc	Fluorescent tube, T5, Daylight, 8 watts with holder
35	200	pc	Fluorescent tube, T8, Daylight, 10 watts
36	100	pc	Fluorescent tube holder for T5
37	250	pc	T8 fluorescent tube socket/lamp holder
38	1500	pc	Incandescent bulb, round, <i>10 to 15 W</i>
39	230	pc	High Power LED bulbs, min. of 27 watts, <i>min. of 2700 lumens, warmwhite, 100-240VAC, 150 degrees beam angle, minimum of 15000 burning hours</i>
40	125	pc	LED spotlight, min. of 9 watts (as per sample)
41	35	pc	LED Electronic driver, <i>Philip Advance Lighting</i> <i>Power factor: 0.95</i> <i>Power output: 150 watts</i> <i>Input voltage: 120 to 277 VAC, 50/60Hz</i> <i>Output voltage: 107 to 214 Vdc</i> <i>Ballast dimming: Yes</i> <i>Dimming type: 0-10V dimming</i> <i>Output current: 0.7 Adc or higher</i>
42	22	pc	LED street light, min. of 80watts, 230VAC <i>Luminous flux: Min. of 9,600 lm</i> <i>Light source: 2 layer of high brightness LED SMD</i> <i>Color Temperature: Warm White</i> <i>Materials: Die cast aluminum alloy</i> <i>Lifetime: 50,000 hours</i> <i>IP Rating: IP65</i>
43	1200	pc	LED tubes, 15-18 watts, <i>Length: 1.2m</i> <i>Input voltage: 220V (without ballast)</i> <i>Beam angle: at least 180 degrees</i> <i>color Temp.: Daylight</i> <i>Difuser: Frosted poly carbonated cover</i> <i>Min. lifetime: 50000 hours</i> <i>Min. flux: 100 lm</i> <i>Offered brand must be rosh and UL/ETL approved</i>
44	150	pc	LED tubes, 4 to 6 watts, <i>Length: 1 ft</i> <i>Input voltage: 220V (without ballast)</i> <i>Beam angle: at least 180 degrees</i> <i>color Temp.: Daylight</i> <i>Difuser: Frosted poly carbonated cover</i> <i>Min. lifetime: 50000 hours</i> <i>Min. flux: 100 lm</i> <i>Offered brand must be rosh and UL/ETL approved</i>
<b>Lot III - SUPPLY AND DELIVERY OF WIRES AND CABLES (offered brand must have PS mark)</b>			
45	4	roll	Royal Cord, 3 Conductor, AWG #16, 75 m/roll
46	4	roll	Flat Cord, AWG #16, black
47	4	roll	Flat Cord, AWG #18, black

48	9	roll	THHN Wire, 2.0mm2
49	4	roll	TW/TF Wire, AWG #18, Solid
50	57	roll	TF wire, AWG#16, 150m/roll
<b>Lot IV - SUPPLY AND DELIVERY OF ELECTRONICS MATERIALS</b>			
51	40	pc	Telephone handset, wall mounted, trimstyle, corded, analog
52	12	roll	Telephone cable, 2-pair, copper, 24AWG, PE insulation with aluminum/polyesterfoil shielding, PVC outer sheath
53	71	pc	Telephone outlet, 1-gang, with cover plate
54	151	pc	RJ22 telephone connector, 4-pin
55	3	pc	DMX Controller 384 output channels 30 banks have 8 programmable scenes Record up to 6 programmable chases with fade time and speed LED function and program display DMX in/out: 3 pin male/female XLR Power input: DC 9V, 1000mA Certification: CE and RoHS
56	40	pc	Toggle Switch, DPDT
57	150	pc	RJ9 connector, 4p4c plug telephone jack connector for telephone headset modular plug jack
58	25	pc	RJ9 to 3.5mm headset adapter,
59	25	pc	Headset with microphone, stereo, noise-cancelling microphone, volume control in line, superior ear cushion, self adjusting leather inner headband, 3.5mm audio jack connection Speaker: 50mm Frequency range: 20Hz to 20kHz impedance: 32 ohms Sensitivity: 109dB Cable length: 1.8m
60	200	pc	Battery, alkaline, size "AA"
61	152	pc	Battery, Alkaline, Size "AAA"
62	180	pc	Battery, Alkaline, 9V
63	10	pc	Wireless HDMI dongle, wireless video transmitter and receiver, CPU single core ARM cortex A9 rockship RK2928 1.2 GHz OS : Linux 3.0.8 DDR3: 256 MB Support miracast/mirror System: Android, Mac, Windows Support photo format: JPEG, BMP DC supply: supply from USB Projector: support projector with HDMI interface
64	80	pc	Relay, DPDT, 12VDC, 10A, PCB type
65	10	pc	Relay, DPDT, 24VDC, 10A, PCB type
66	20	pc	Auto Door Ball Switch
67	2	pc	Power supply, 220VAC in, 24VDC out, 20A
68	30	pc	Limit switch, SPDT, 15A, 250VAC
69	1	lot	Electronic parts and accessories 8 pcs PCB board, 15cm x 20cm, double sided copper

		prototype 240pcs LED, superbright, white, 5mm 12 pcs Relay, 240V, 10A, DPDT 16 pcs Capacitor, 10 $\mu$ F/35 Volts, polarized 16 pcs Capacitor, 2200 $\mu$ F/35Volts, polarized 12 pcs Transistor, 2N4401NPN 24 pcs Diode, IN4004 24 pcs Resistor, 5kilo ohms, 1watts	
--	--	---	--

STATEMENT OF COMPLIANCE

*Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered.*

**Note:**

*Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.*



**Cost Breakdown**

<b>Item No.</b>	<b>Qty.</b>	<b>Unit</b>	<b>Article /Description</b>	<b>Unit Price</b>	<b>Total Amount</b>
<b>Lot I - SUPPLY AND DELIVERY OF ELECTRICAL MATERIALS</b>					
1	99	pc	Lamp Holder, e27, with built-in induction motion sensor switch, 110 to 220VAC, at least 60 watts rated load, 6 meter detection range, adjustable light delay time out from 10 second to 5 minutes		
2	10	pc	Penetrating oil, minimum of 400mL		
3	80	pc.	Plug, 2-prong, parallel, heavy duty		
4	25	pack	Cable tie (nylon), 2.5-3.0mm x 6" long (100pcs/pack)		
5	25	pack	Cable tie (nylon), 4.0mm x 12" long (100pcs/pack)		
6	25	pack	Cable tie (nylon), 4.0mm x 8" long (100pcs/pack)		
7	25	pack	Cable tie (nylon), 5.0mm x 12" long (100pcs/pack)		
8	10	can	Spray paint, epoxy primer, gray, 400cc		
9	40	kg	Rags, cotton, white		
10	35	pc	Globe/round acrylic diffuser, clear, 14" diameter		
11	1400	roll	Electrical Tape, PVC, 0.16mm x 19mm x 16 m (min.), UL listed		
12	15	box	Gun tucker staple wire, T25		
13	200	pc	PVC electrical conduiti, 1" dia		
14	78	pc	PVC elbow, <i>90 degrees</i> 1" dia		
15	70	pc	PVC junction box with cover, 4" x 4", 1" dia		
16	140	pc	PVC male adapter with nut, 1" dia		
17	100	pc	PVC coupling, 1" dia		
18	266	pc	PVC electrical conduiti, 1/2" dia		
19	44	pc	PVC elbow, <i>90 degrees</i> 1/2" dia		
20	87	pc	PVC junction box with cover, 4" x 4", 1/2" dia		
21	174	pc	PVC male adapter with nut, 1/2" dia		
22	100	pc	PVC coupling, 1/2" dia		
23	166	pc	Electrical metallic tubing (EMT), 1/2" dia		
24	50	pc	EMT elbow, <i>90 degrees</i> 1/2" dia		
25	60	pc	EMT junction box, 4"x4", 1/2" dia		
26	120	pc	EMT male adapter with nut, 1/2" dia		
27	140	pc	EMT coupling, 1/2" dia		
28	320	pc	C-metal clamp, 1/2" dia		
29	1	pc	NEMA 4X enclosure with cover		
30	5	kg	GI wire #16		
31	50	pair	Construction gloves		
32	1000	pc	Metal screw with tox, Size #10		

33	10	unit	Automatic Voltage Regulator, 300VA, Input-160-240VAC, 6Hz, Output Voltage - 100 and 220VAC, 60Hz		
				<b>Sub – total</b>	
<b>Lot II - SUPPLY AND DELIVERY OF LIGHTING MATERIALS</b>					
34	150	pc	Fluorescent tube, T5, Daylight, 8 watts with holder		
35	200	pc	Fluorescent tube, T8, Daylight, 10 watts		
36	100	pc	Fluorescent tube holder for T5		
37	250	pc	T8 fluorescent tube socket/lamp holder		
38	1500	pc	Incandescent bulb, round, <i>10 to 15 W</i>		
39	230	pc	High Power LED bulbs, min. of 27 watts <i>min. of 2700 lumens, warmwhite, 100-240VAC, 150 degrees beam angle, minimum of 15000 burning hours</i>		
40	125	pc	LED spotlight, min. of 9 watts (as per sample)		
41	35	pc	LED Electronic driver, <i>Philip Advance Lighting</i> <i>Power factor: 0.95</i> <i>Power output: 150 watts</i> <i>Input voltage: 120 to 277 VAC, 50/60Hz</i> <i>Output voltage: 107 to 214 Vdc</i> <i>Ballast dimming: Yes</i> <i>Dimming type: 0-10V dimming</i> <i>Output current: 0.7 A dc or higher</i>		
42	22	pc	LED street light, min. of 80watts, 230VAC <i>Luminous flux: Min. of 9,600 lm</i> <i>Light source: 2 layer of high brightness LED SMD</i> <i>Color Temperature: Warm White</i> <i>Materials: Die cast aluminum alloy</i> <i>Lifetime: 50,000 hours</i> <i>IP Rating: IP65</i>		
43	1200	pc	LED tubes, 15-18 watts, <i>Length: 1.2m</i> <i>Input voltage: 220V (without ballast)</i> <i>Beam angle: at least 180 degrees</i> <i>color Temp.: Daylight</i> <i>Difuser: Frosted poly carbonated cover</i> <i>Min. lifetime: 50000 hours</i> <i>Min. flux: 100 lm</i> <i>Offered brand must be rosh and UL/ETL approved</i>		
44	150	pc	LED tubes, 4 to 6 watts, <i>Length: 1 ft</i> <i>Input voltage: 220V (without ballast)</i> <i>Beam angle: at least 180 degrees</i> <i>color Temp.: Daylight</i>		

			<i>Difuser: Frosted poly carbonated cover Min. lifetime: 50000 hours Min. flux: 100 lm Offered brand must be rosh and UL/ETL approved</i>		
				<b>Sub – total</b>	
<b>Lot III – SUPPLY AND DELIVERY OF WIRES AND CABLES (offered brand must have PS mark)</b>					
45	4	roll	Royal Cord, 3 Conductor, AWG #16, 75 m/roll		
46	4	roll	Flat Cord, AWG #16, black		
47	4	roll	Flat Cord, AWG #18, black		
48	9	roll	THHN Wire, 2.0mm2		
49	4	roll	TW/TF Wire, AWG #18, Solid		
50	57	roll	TF wire, AWG#16, 150m/roll		
<b>Lot IV – SUPPLY AND DELIVERY OF ELECTRONICS MATERIALS</b>					
51	40	pc	Telephone handset, wall mounted, trimstyle, corded, analog		
52	12	roll	Telephone cable, 2-pair, copper, 24AWG, PE insulation with aluminum/polyesterfoil shielding, PVC outer sheath		
53	71	pc	Telephone outlet, 1-gang, with cover plate		
54	151	pc	RJ22 telephone connector, 4-pin		
55	3	pc	DMX Controller 384 output channels 30 banks have 8 programmable scenes Record up to 6 programmable chases with fade time and speed LED function and program display DMX in/out: 3 pin male/female XLR Power input: DC 9V, 1000mA Certification: CE and RoHS		
56	40	pc	Toggle Switch, DPDT		
57	150	pc	RJ9 connector, 4p4c plug telephone jack connector for telephone headset modular plug jack		
58	25	pc	RJ9 to 3.5mm headset adapter,		
59	25	pc	Headset with microphone, stereo, noise-cancelling microphone, volume control in line, superior ear cushion, self adjusting leather inner headband, 3.5mm audio jack connection Speaker: 50mm Frequency range: 20Hz to 20kHz impedance: 32 ohms Sensitivity: 109dB Cable length: 1.8m		

60	200	pc	Battery, alkaline, size "AA"		
61	152	pc	Battery, Alkaline, Size "AAA"		
62	180	pc	Battery, Alkaline, 9V		
63	10	pc	Wireless HDMI dongle, wireless video transmitter and receiver, CPU single core ARM cortex A9 rockship RK2928 1.2 GHz OS : Linux 3.0.8 DDR3: 256 MB Support miracast/mirror System: Android, Mac, Windows Support photo format: JPEG, BMP DC supply: supply from USB Projector: support projector with HDMI interface		
64	80	pc	Relay, DPDT, 12VDC, 10A, PCB type		
65	10	pc	Relay, DPDT, 24VDC, 10A, PCB type		
66	20	pc	Auto Door Ball Switch		
67	2	pc	Power supply, 220VAC in, 24VDC out, 20A		
68	30	pc	Limit switch, SPDT, 15A, 250VAC		
69	1	lot	Electronic parts and accessories 8 pcs PCB board, 15cm x 20cm, double sided copper prototype 240pcs LED, superbright, white, 5mm 12 pcs Relay, 240V, 10A, DPDT 16 pcs Capacitor, 10 $\mu$ F/35 Volts, polarized 16 pcs Capacitor, 2200 $\mu$ F/35Volts, polarized 12 pcs Transistor, 2N4401NPN 24 pcs Diode, IN4004 24 pcs Resistor, 5kilo ohms, 1watts		
<b>Sub - total</b>					

Prepared by:

\_\_\_\_\_  
Signature over printed name of Authorized Representative

\_\_\_\_\_  
Position

\_\_\_\_\_  
Date